FieldLink process networking AS-Interface

Masters and gateways

Model number GW458116A

AS-Interface to ProfiNet gateway

The AS-Interface/ProfiNet gateway interfaces the AS-Interface to ProfiNet. The gateway acts as a master for AS-Interface and as a slave for ProfiNet. AS-Interface functions can be called up via ProfiNet. Commissioning can be accomplished with a hand-held addressing unit or with the push buttons on the gateway.

Features

- · Duplicate address detection
- Version 3.0 master-compatible with all 2.0 and 3.0 slaves and 7.3 profile analog modules
- AS-Interface peripheral fault diagnostics
- Serial diagnostics port: see SW462008A for software and cable





Specifications	
AS-Interface master version	3.0
Interface	ProfiNet (RJ-45 Ethernet)
Operating current	300mA (from AS-Interface circuit)
Operating voltage	30 VDC AS-Interface voltage (AS-Interface power supply)
Baud rate	10/100m baud (automatic recognition)
AS-Interface cycle time	Cycle time = 150 microsec. x (AS-Interface slaves +2)
Displays	LCD display Power on, green LED Serial communication active, green LED Configuration error, red LED AS-Interface voltage normal, green LED AS-Interface normal operation, green LED Automatic address program enabled, green LED Master in configuration mode, yellow LED
Operating temperature	0° to +55°C (+32° to +131°F)
Storage temperature	-25° to +85°C (-13° to +185°F)
Housing Dimensions (L, W, H) Ingress protection	Stainless steel, DIN rail mounting 120mm, 100mm, 83mm IP20, field enclosure required
Weight	550g (1.2 pounds)





Schematic drawing Serial diagnostics port ProfiNet RJ-45


Graphical display

The interactive graphical display on this gateway enables the entire AS-Interface network to be commissioned and the connected devices to be completely tested without a PC, PLC or host system. It also enables the user to complete all tasks previously requiring the "AS-Interface Control Tools" software package or hand-held. This allows for simpler and faster commissioning.

Features

17

- Set device addresses
- Test inputs and outputs
- Perform network diagnostics
- · View error counter



Valmet's professionals around the world work close to our customers and are committed to moving our customers' performance forward – every day.

Valmet Flow Control Oy

Vanha Porvoontie 229 01380 Vantaa, Finland flowcontrol@valmet.com +358 10 417 5000 valmet.com/flowcontrol

Valmet Flow Control Inc. Stonel product center

26271 US Hwy 59, Fergus Falls, MN 56537 USA. Tel. +1 218 739 5774. sales.stonel@valmet.com valmet.com/flowcontrol



